

Architecture de Réseaux

Travaux Pratiques

AINA Alain Patrick


AfNOG V

dakar, 17-21 mai 2004

aalain@trstech.net

Africa Network Operators Group

TP CONCEPTION DE RESEAU



© 2001, Cisco Systems, Inc. All rights reserved.

1

- Connectez les interfaces de votre routeur sur chacun des switch (e0/0 sur sw1 et e0/1 vers sw2)
- Adresses a utiliser pour les interfaces Ethernet
Sw1: 84.201.92.0/25 (3-126)
Sw2: 84.201.92.128/25(131-254)
- Configurez le loopback 84.210.94.x/32
- Activer OSPF sur votre routeur avec authentification
- Injectez les préfixes de loopback et de vos connexions Ethernet dans OSPF
- Les routeurs du Noyau injectent du default
- Quels sont les préfixes disponibles dans OSPF?
- Faire des traceroute vers les loopback et vers Internet a partir de vos routeurs
- Simulez des pannes de switch et de routeur

© 2001, Cisco Systems, Inc. All rights reserved.

1

TP HSRP

Agenda




- **HSRP- 1 groupe**
- **HSRP- 2 groupes**
- **Tracking interface**
- **Preempt delay**

Topologie Physique



Africa Network Operator's Group



© 2001, Cisco Systems, Inc. All rights reserved.


1

Adressage IP



Africa Network Operator's Group

Groupe impair : 84.201.64.0/23




© 2001, Cisco Systems, Inc. All rights reserved.

1

Routage



Africa Network Operator's Group




© 2001, Cisco Systems, Inc. All rights reserved.

1

HSRP – 1 Router Group



Africa Network Operator's Group



- Router Groupe impair : actif
- Router Groupe pair : standby


© 2001, Cisco Systems, Inc. All rights reserved.

1

HSRP – 2 Router Group



Africa Network Operator's Group




© 2001, Cisco Systems, Inc. All rights reserved.

1

Routage



Africa Network Operator's Group




© 2001, Cisco Systems, Inc. All rights reserved.

1

HSRP – Tracking interface



Africa Network Operators Group



- Tracking interface Eth0/1
- Debrancher Eth0/1

© 2001, Cisco Systems, Inc. All rights reserved.

1

HSRP - configuration



Africa Network Operators Group

```
Router1:  
interface ethernet 0/0  
description LAN serveur  
ip address 84.201.64.3 255.255.240.0  
standby 10 ip 84.201.64.4  
standby 10 track ethernet0/1  
standby 11 priority 150  
standby 11 preempt  
standby 11 ip 84.201.64.5  
standby 11 track ethernet0/1
```

© 2001, Cisco Systems, Inc. All rights reserved.

1

HSRP - configuration



Africa Network Operators Group

```
Router2:  
interface ethernet 0/0  
description LAN serveur  
ip address 84.201.64.6 255.255.240.0  
standby 10 priority 150  
standby 10 preempt  
standby 10 ip 84.201.64.4  
standby 10 track ethernet0/1  
standby 11 ip 84.201.64.5  
standby 11 track ethernet0/1
```

© 2001, Cisco Systems, Inc. All rights reserved.

1