

BGP Scaling Techniques



ISP Workshops

BGP Scaling Techniques

- Original BGP specification and implementation was fine for the Internet of the early 1990s
 - But didn't scale
- Issues as the Internet grew included:
 - Scaling the iBGP mesh beyond a few peers?
 - Implement new policy without causing flaps and route churning?
 - Keep the network stable, scalable, as well as simple?

BGP Scaling Techniques

- Current Best Practice Scaling Techniques
 - Route Refresh
 - Peer-groups
 - Route Reflectors (and Confederations)
- Deprecated Scaling Techniques
 - Soft Reconfiguration
 - Route Flap Damping

Dynamic Reconfiguration



Non-destructive policy changes

Route Refresh

- Policy Changes:
 - Hard BGP peer reset required after every policy change because the router does not store prefixes that are rejected by policy
- Hard BGP peer reset:
 - Tears down BGP peering
 - Consumes CPU
 - Severely disrupts connectivity for all networks
- Solution:
 - Route Refresh

Route Refresh Capability

- ❑ Facilitates non-disruptive policy changes
- ❑ No configuration is needed
 - Automatically negotiated at peer establishment
- ❑ No additional memory is used
- ❑ Requires peering routers to support “route refresh capability” – RFC2918
- ❑ Tell peer to resend full BGP announcement

```
clear ip bgp x.x.x.x [soft] in
```
- ❑ Resend full BGP announcement to peer

```
clear ip bgp x.x.x.x [soft] out
```

Dynamic Reconfiguration

- Use Route Refresh capability
 - Supported on virtually all routers
 - find out from “show ip bgp neighbor”
 - Non-disruptive, “Good For the Internet”


- Only hard-reset a BGP peering as a last resort

Consider the impact to be equivalent to a router reboot

Cisco's Soft Reconfiguration

- ❑ **Now deprecated** — but:
- ❑ Router normally stores prefixes which have been received from peer after policy application
 - Enabling soft-reconfiguration means router also stores prefixes/attributes received prior to any policy application
 - Uses more memory to keep prefixes whose attributes have been changed or have not been accepted
- ❑ Only useful now when operator requires to know which prefixes have been sent to a router prior to the application of any inbound policy

Cisco's Soft Reconfiguration



Configuring Soft Reconfiguration

```
router bgp 100
  neighbor 1.1.1.1 remote-as 101
  neighbor 1.1.1.1 route-map infilter in
  neighbor 1.1.1.1 soft-reconfiguration inbound
! Outbound does not need to be configured !
```

- Then when we change the policy, we issue an exec command

```
clear ip bgp 1.1.1.1 soft [in | out]
```

- Note:

- When “soft reconfiguration” is enabled, there is no access to the route refresh capability
- `clear ip bgp 1.1.1.1 [in | out]` will also do a soft refresh

Peer Groups



Peer Groups

- Problem – how to scale iBGP
 - Large iBGP mesh slow to build
 - iBGP neighbours receive the same update
 - Router CPU wasted on repeat calculations
- Solution – peer-groups
 - Group peers with the same outbound policy
 - Updates are generated once per group

Peer Groups – Advantages

- ❑ Makes configuration easier
- ❑ Makes configuration less prone to error
- ❑ Makes configuration more readable
- ❑ Lower router CPU load
- ❑ iBGP mesh builds more quickly
- ❑ Members can have different inbound policy
- ❑ Can be used for eBGP neighbours too!

Configuring a Peer Group

```
router bgp 100
  neighbor ibgp-peer peer-group
  neighbor ibgp-peer remote-as 100
  neighbor ibgp-peer update-source loopback 0
  neighbor ibgp-peer send-community
  neighbor ibgp-peer route-map outfilter out
  neighbor 1.1.1.1 peer-group ibgp-peer
  neighbor 2.2.2.2 peer-group ibgp-peer
  neighbor 2.2.2.2 route-map infilter in
  neighbor 3.3.3.3 peer-group ibgp-peer
```

! note how 2.2.2.2 has different inbound filter from peer-group !

Configuring a Peer Group

```
router bgp 100
  neighbor external-peer peer-group
  neighbor external-peer send-community
  neighbor external-peer route-map set-metric out
  neighbor 160.89.1.2 remote-as 200
  neighbor 160.89.1.2 peer-group external-peer
  neighbor 160.89.1.4 remote-as 300
  neighbor 160.89.1.4 peer-group external-peer
  neighbor 160.89.1.6 remote-as 400
  neighbor 160.89.1.6 peer-group external-peer
  neighbor 160.89.1.6 filter-list infilter in
```

Peer Groups

- Always configure peer-groups for iBGP
 - Even if there are only a few iBGP peers
 - Easier to scale network in the future
- Consider using peer-groups for eBGP
 - Especially useful for multiple BGP customers using same AS (RFC2270)
 - Also useful at Exchange Points where ISP policy is generally the same to each peer
- Peer-groups are essentially obsolete
 - But are still widely considered best practice
 - Replaced by update-groups (internal coding – not configurable)
 - Enhanced by peer-templates (allowing more complex constructs)

Route Reflectors




Scaling the iBGP mesh

Scaling iBGP mesh


- Avoid $\frac{1}{2}n(n-1)$ iBGP mesh

**$n=1000 \Rightarrow$ nearly
half a million
ibgp sessions!**




- Two solutions
 - Route reflector – simpler to deploy and run
 - Confederation – more complex, has corner case advantages

Route Reflector: Principle




Route Reflector: Principle



Route Reflector

- ❑ Reflector receives path from clients and non-clients
- ❑ Selects best path
- ❑ If best path is from client, reflect to other clients and non-clients
- ❑ If best path is from non-client, reflect to clients only
- ❑ Non-meshed clients
- ❑ Described in RFC4456



Route Reflector Topology

- ❑ Divide the backbone into multiple clusters
- ❑ At least one route reflector and few clients per cluster
- ❑ Route reflectors are fully meshed
- ❑ Clients in a cluster could be fully meshed
- ❑ Single IGP to carry next hop and local routes


Route Reflectors: Loop Avoidance

- ❑ Originator_ID attribute
 - Carries the RID of the originator of the route in the local AS (created by the RR)
- ❑ Cluster_list attribute
 - The local cluster-id is added when the update is sent by the RR
 - Cluster-id is router-id by default (usually the address of loopback interface)
 - **Do NOT use** `bgp cluster-id x.x.x.x` unless the two route reflectors are **physically/directly** connected

Route Reflectors: Redundancy

- Multiple RRs can be configured in the same cluster – not advised!
 - All RRs in the cluster must have the same cluster-id (otherwise it is a different cluster)
- A router may be a client of RRs in different clusters
 - Common today in ISP networks to overlay two clusters – redundancy achieved that way
 - → Each client has two RRs = redundancy

Route Reflectors: Redundancy



Cluster One

Cluster Two




Route Reflector: Benefits

- ❑ Solves iBGP mesh problem
- ❑ Packet forwarding is not affected
- ❑ Normal BGP speakers co-exist
- ❑ Multiple reflectors for redundancy
- ❑ Easy migration
- ❑ Multiple levels of route reflectors

Route Reflectors: Migration

- Where to place the route reflectors?
 - Follow the physical topology!
 - This will guarantee that the packet forwarding won't be affected
- Configure one RR at a time
 - Eliminate redundant iBGP sessions
 - Place one RR per cluster

Route Reflectors: Migration



- ❑ Migrate small parts of the network, one part at a time.

Configuring a Route Reflector

□ Router D configuration:

```
router bgp 100
...
neighbor 1.2.3.4 remote-as 100
neighbor 1.2.3.4 route-reflector-client
neighbor 1.2.3.5 remote-as 100
neighbor 1.2.3.5 route-reflector-client
neighbor 1.2.3.6 remote-as 100
neighbor 1.2.3.6 route-reflector-client
...
```

BGP Scaling Techniques

- These 3 techniques should be core requirements on all ISP networks
 - Route Refresh (or Soft Reconfiguration)
 - Peer groups
 - Route Reflectors

BGP Confederations




Confederations

- Divide the AS into sub-AS
 - eBGP between sub-AS, but some iBGP information is kept
 - Preserve NEXT_HOP across the sub-AS (IGP carries this information)
 - Preserve LOCAL_PREF and MED
- Usually a single IGP
- Described in RFC5065

Confederations

- Visible to outside world as single AS – “Confederation Identifier”
 - Each sub-AS uses a number from the private space (64512-65534)
- iBGP speakers in sub-AS are fully meshed
 - The total number of neighbors is reduced by limiting the full mesh requirement to only the peers in the sub-AS


Confederations



□ Configuration (Router C):

```
router bgp 65532
  bgp confederation identifier 200
  bgp confederation peers 65530 65531
  neighbor 141.153.12.1 remote-as 65530
  neighbor 141.153.17.2 remote-as 65531
```

Confederations: Next Hop






Confederation: Principle

- ❑ Local preference and MED influence path selection
- ❑ Preserve local preference and MED across sub-AS boundary
- ❑ Sub-AS eBGP path administrative distance

Confederations: Loop Avoidance

- ❑ Sub-AS traversed are carried as part of AS-path
- ❑ AS-sequence and AS path length
- ❑ Confederation boundary
- ❑ AS-sequence should be skipped during MED comparison

Confederations: AS-Sequence



Route Propagation Decisions

- Same as with “normal” BGP:
 - From peer in same sub-AS → only to external peers
 - From external peers → to all neighbors
- “External peers” refers to
 - Peers outside the confederation
 - Peers in a different sub-AS
 - Preserve LOCAL_PREF, MED and NEXT_HOP

Confederations (cont.)

□ Example (cont.):

BGP table version is 78, local router ID is 141.153.17.1

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal

Origin codes: i - IGP, e - EGP, ? - incomplete

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 10.0.0.0	141.153.14.3	0	100	0	(65531) 1 i
*> 141.153.0.0	141.153.30.2	0	100	0	(65530) i
*> 144.10.0.0	141.153.12.1	0	100	0	(65530) i
*> 199.10.10.0	141.153.29.2	0	100	0	(65530) 1 i

More points about confederations

- Can ease “absorbing” other ISPs into your ISP
 - e.g., if one ISP buys another
 - (can use local-as feature to do a similar thing)
- You can use route-reflectors with confederation sub-AS to reduce the sub-AS iBGP mesh

Confederations: Benefits

- ❑ Solves iBGP mesh problem
- ❑ Packet forwarding not affected
- ❑ Can be used with route reflectors
- ❑ Policies could be applied to route traffic between sub-AS' s

Confederations: Caveats

- ❑ Minimal number of sub-AS
- ❑ Sub-AS hierarchy
- ❑ Minimal inter-connectivity between sub-AS' s
- ❑ Path diversity
- ❑ Difficult migration
 - BGP reconfigured into sub-AS
 - must be applied across the network

RRs or Confederations

	Internet Connectivity	Multi-Level Hierarchy	Policy Control	Scalability	Migration Complexity
Confederations	Anywhere in the Network	Yes	Yes	Medium	Medium to High
Route Reflectors	Anywhere in the Network	Yes	Yes	Very High	Very Low

Most new service provider networks now deploy Route Reflectors from Day One

Route Flap Damping



Network Stability for the 1990s

Network Instability for the 21st
Century!

Route Flap Damping

- ❑ For many years, Route Flap Damping was a strongly recommended practice
- ❑ Now it is strongly discouraged as it causes far greater network instability than it cures
- ❑ But first, the theory...

Route Flap Damping

- Route flap
 - Going up and down of path or change in attribute
 - BGP WITHDRAW followed by UPDATE = 1 flap
 - eBGP neighbour going down/up is NOT a flap
 - Ripples through the entire Internet
 - Wastes CPU
- Damping aims to reduce scope of route flap propagation


Route Flap Damping (continued)

- Requirements
 - Fast convergence for normal route changes
 - History predicts future behaviour
 - Suppress oscillating routes
 - Advertise stable routes
- Implementation described in RFC 2439

Operation

- Add penalty (1000) for each flap
 - Change in attribute gets penalty of 500
- Exponentially decay penalty
 - half life determines decay rate
- Penalty above suppress-limit
 - do not advertise route to BGP peers
- Penalty decayed below reuse-limit
 - re-advertise route to BGP peers
 - penalty reset to zero when it is half of reuse-limit

Operation



Operation

- ❑ Only applied to inbound announcements from eBGP peers
- ❑ Alternate paths still usable
- ❑ Controlled by:
 - Half-life (default 15 minutes)
 - reuse-limit (default 750)
 - suppress-limit (default 2000)
 - maximum suppress time (default 60 minutes)

Configuration

- ❑ Fixed damping

```
router bgp 100
```

```
  bgp dampening [<half-life> <reuse-value> <suppress-  
    penalty> <maximum suppress time>]
```

- ❑ Selective and variable damping

```
  bgp dampening [route-map <name>]
```

```
    route-map <name> permit 10
```

```
      match ip address prefix-list FLAP-LIST
```

```
      set dampening [<half-life> <reuse-value>  
        <suppress-penalty> <maximum suppress time>]
```

```
    ip prefix-list FLAP-LIST permit 192.0.2.0/24 le 32
```

Operation

- ❑ Care required when setting parameters
- ❑ Penalty must be less than reuse-limit at the maximum suppress time
- ❑ Maximum suppress time and half life must allow penalty to be larger than suppress limit

Configuration

□ Examples – ✘

■ bgp dampening 15 500 2500 30

- reuse-limit of 500 means maximum possible penalty is 2000 – no prefixes suppressed as penalty cannot exceed suppress-limit

□ Examples – ✔

■ bgp dampening 15 750 3000 45

- reuse-limit of 750 means maximum possible penalty is 6000 – suppress limit is easily reached

Maths!

- Maximum value of penalty is

$$\text{max-penalty} = \text{reuse-limit} \times 2^{\left(\frac{\text{max-suppress-time}}{\text{half-life}} \right)}$$

- Always make sure that suppress-limit is LESS than max-penalty otherwise there will be no route damping

Route Flap Damping History

- First implementations on the Internet by 1995
- Vendor defaults too severe
 - RIPE Routing Working Group recommendations in ripe-178, ripe-210, and ripe-229
 - <http://www.ripe.net/ripe/docs>
 - But many ISPs simply switched on the vendors' default values without thinking

Serious Problems:

- "Route Flap Damping Exacerbates Internet Routing Convergence"
 - Zhuoqing Morley Mao, Ramesh Govindan, George Varghese & Randy H. Katz, August 2002
- "What is the sound of one route flapping?"
 - Tim Griffin, June 2002
- Various work on routing convergence by Craig Labovitz and Abha Ahuja a few years ago
- "Happy Packets"
 - Closely related work by Randy Bush et al

Problem 1:

- One path flaps:
 - BGP speakers pick next best path, announce to all peers, flap counter incremented
 - Those peers see change in best path, flap counter incremented
 - After a few hops, peers see multiple changes simply caused by a single flap → prefix is suppressed

Problem 2:

- Different BGP implementations have different transit time for prefixes
 - Some hold onto prefix for some time before advertising
 - Others advertise immediately
- Race to the finish line causes appearance of flapping, caused by a simple announcement or path change → prefix is suppressed

Solution:

- ❑ Misconfigured Route Flap Damping will seriously impact access to:
 - Your network and
 - The Internet
- ❑ More background contained in RIPE Routing Working Group document:
 - www.ripe.net/ripe/docs/ripe-378
- ❑ Recommendations now in:
 - www.rfc-editor.org/rfc/rfc7196.txt and www.ripe.net/ripe/docs/ripe-580

BGP Scaling Techniques



ISP Workshops